



---

**SPECIFICATION  
SAMPSON MILLS SYSTEM  
#F16 HAND OPERATED RECESSED DRAPERY TRACK**

**Part 1 -General**

**1.01 SUMMARY**

A. Work of this section includes hand operated window treatment hardware as manufactured by Sampson Mills Ltd.

**1.02 SUBMITTALS**

A. Product data: Manufacturer's descriptive literature shall be submitted, indicating materials, finishes and installation instructions for each type of window treatment specified.

B. Shop drawings: Components and installation detail drawings shall be supplied as requested.

C. There must be only one single extrusion.

C1. The carriers must be able to be inserted or removed from the profile after install.

C2. When spliced, any section must be able to be removed without effecting the other sections.

C3. This System selected specifically because there is no front and back

C3a it looks identical from the window side (outside) or room side

C3b. It looks identical from both sides when used as room dividers.

**1.03 QUALITY ASSURANCE**

A. Products shall be manufactured to meet or exceed all quality standards as stipulated by Sampson Mills.

B. Product specifically designed for labor reduction and for easy maintenance and repair. Quality and labor savings must be equal or greater approved solutions by manufacturer Sampson Mills.

**1.04 DELIVERY, STORAGE AND HANDLING**

A. Product shall be delivered to the project site in manufacturer's original packaging.

B. Product shall be handled and stored to prevent damage to materials, finishes and operating mechanisms.

**1.05 WARRANTY**

A. Manufacturer shall provide that F16 system components are free of defects for **Five** years from the date of shipping. Specific product warranty terms are available from Sampson Mills.

**Part 2 -Product**

**2.01 MANUFACTURER**

A. Acceptable product: Window treatment system, #F16 HAND OPERATED DRAPERY TRACK as manufactured by: Sampson Mills Ltd. P.O. Box 1147 New York, 10150

**2.02 EQUIPMENT**

A. medium to heavy duty hand recessed operated drapery track which shall accommodate Wave, pinch pleat, grommet, or S-Fold drapery headings. (select drapery heading)

**2.03 COMPONENTS**

A. Track:

1. Shall be T6 anodized aluminum (optional: Sampson Mills approved powder coated finish) ,

1a Standard Colors Black, White, Silver

1b Custom colors available upon approval and request.

2. Curve-able on both inside and outside radii, to a minimum radius of 10" For F16

3. Project site and drawings specifically designed for exterior dimensions of profiles Cad or pdf drawings available upon request.

4. Profiles and finishes must be rated for indoor & outdoor use.

B. Parts:

1. System shall include ceiling mount screws to install through the center of the track channel

3. Must use PP28 Profile protector when installing to ensure no damage to the channels

3a. To be provided with every assembled order.

4. Must use DB6 Square drive bit and SC41-6T Screws to be provided with every assembled order.

5. 3mm or 1/8" drill bit recommended for drilling through track.

6. Shall be original Sampson Mills components.

C. Drapery Heading Systems Options:

1. Standard Free-Flow Heading System

1a. Shall be original Sampson Mills components or others approved by Sampson Mills.



# Sampson Mills Ltd.

**Sampson Mills Ltd.**  
P.O. Box 1147  
New York, 10150

Phone: (718) 412-9040  
Fax: (718) 412-9039

info@Sampsonmills.com  
www.Sampsonmills.com

---

2. Drapery S-Heading System
  - 2a. Shall be original Sampson Mills components or others approved by Sampson Mills.
3. Pinch Pleat Heading Systems:
  - 3a. Shall be original Sampson Mills components or others approved by Sampson Mills.
4. Grommet Heading Systems:
  - 4a. Shall be original Sampson Mills components or others approved by Sampson Mills.

### **Part 3 -Execution**

#### **3.01 INSTALLATION**

- A. Install window treatment system in accordance with Sampson Mills specifications, standards and procedures. Installation contractor shall be responsible for site measurements and suitability of mounting surface.
- B. Adequate clearance shall be provided to permit unencumbered operation of the entire system.
- C. To prevent damage to the track, the Profile protector included with the track must be used during installation.
- D. System can also be installed with a nail gun into the flanges adhesive on the back of the track optional.
- E. When mudding in the track use 0.5" masking tape to protect the track channel from the plaster.

**Manufacturer:** Sampson Mills Ltd  
718-412-9040  
[info@sampsonmills.com](mailto:info@sampsonmills.com)  
PO Box 1147  
New York NY 10150

**technical counsel:**  
Joseph Bibi  
718-412-9040; 415  
[Joseph@sampsonmills.com](mailto:Joseph@sampsonmills.com)