



---

**SPECIFICATION  
SAMPSON MILLS SYSTEM  
#FS16 HAND OPERATED DRAPERY TRACK**

**Part 1 -General**

**1.01 SUMMARY**

A. Work of this section includes hand operated window treatment hardware as manufactured by Sampson Mills Ltd.

**1.02 SUBMITTALS**

A. Product data: Manufacturer's descriptive literature shall be submitted, indicating materials, finishes and installation instructions for each type of window treatment specified.

B. Shop drawings: Components and installation detail drawings shall be supplied as requested.

C. When spliced, any section must be able to be removed without effecting the other sections.

**1.03 QUALITY ASSURANCE**

A. Products shall be manufactured to meet or exceed all quality standards as stipulated by Sampson Mills.

B. Product specifically designed for labor reduction and for easy maintenance and repair. Quality and labor savings must be equal or greater approved solutions by manufacturer Sampson Mills.

**1.04 DELIVERY, STORAGE AND HANDLING**

A. Product shall be delivered to the project site in manufacturer's original packaging.

B. Product shall be handled and stored to prevent damage to materials, finishes and operating mechanisms.

**1.05 WARRANTY**

A. Manufacturer shall provide that FS16 system components are free of defects for **Five** years from the date of shipping. Specific product warranty terms are available from Sampson Mills.

**Part 2 -Product**

**2.01 MANUFACTURER**

A. Acceptable product: Window treatment system, #FS16 HAND OPERATED DRAPERY TRACK as manufactured by: Sampson Mills Ltd. P.O. Box 1147 New York, 10150

**2.02 COMPONENTS**

A. Track:

1. Shall be T6 anodized aluminum (optional: Sampson Mills approved powder coated finish) ,
  - 1a Standard Colors Black, White, Silver
  - 1b Custom colors available upon approval and request.
2. Curve-able on both inside and outside radii, to a minimum radius of 4 ¼" For FS16
3. Project site and drawings specifically designed for exterior dimensions of profiles Cad or pdf drawings available upon request.
4. Profiles and finishes must be rated for indoor & outdoor use.

B. Parts:

1. System shall include ceiling mount screws to install through the center of the track channel
3. Must use PP28 Profile protector when installing to ensure no damage to the channels
  - 3a. To be provided with every assembled order.
4. Must use PDB4 Philips drill bit to be provided with every assembled order.
5. Shall be original Sampson Mills components.

C. Drapery Heading Systems Options:

1. Standard Free-Flow Heading System
  - 1a. Shall be original Sampson Mills components or others approved by Sampson Mills.
2. Drapery S-Heading System
  - 2a. Shall be original Sampson Mills components or others approved by Sampson Mills.
3. Pinch Pleat Heading Systems:
  - 3a. Shall be original Sampson Mills components or others approved by Sampson Mills.
4. Grommet Heading Systems:
  - 4a. Shall be original Sampson Mills components or others approved by Sampson Mills.

**Part 3 -Execution**



# Sampson Mills Ltd.

**Sampson Mills Ltd.**  
P.O. Box 1147  
New York, 10150

Phone: (718) 412-9040  
Fax: (718) 412-9039

info@Sampsonmills.com  
www.Sampsonmills.com

---

### 3.01 INSTALLATION

- A. Install window treatment system in accordance with Sampson Mills specifications, standards and procedures. Installation contractor shall be responsible for site measurements and suitability of mounting surface.
- B. Adequate clearance shall be provided to permit unencumbered operation of the entire system.
- C. To prevent damage to the track, the Profile protector included with the track must be used during installation.

**Manufacturer:** Sampson Mills Ltd  
718-412-9040  
[info@sampsonmills.com](mailto:info@sampsonmills.com)  
PO Box 1147  
New York NY 10150

**technical counsel:**  
Joseph Bibi  
718-412-9040; 415  
[Joseph@sampsonmills.com](mailto:Joseph@sampsonmills.com)