



Sampson Mills Ltd.
P.O. Box 1147
New York, 10150

Phone: (718) 412-9040
Fax: (718) 412-9039

info@Sampsonmills.com
www.Sampsonmills.com

**SPECIFICATION
SAMPSON MILLS SYSTEM
THE SHUTTLE (Recessed)
#PF121R HAND OPERATED FLAT PANELTRACK**

Part 1 -General

1.01 SUMMARY

A. Work of this section includes hand operated window treatment and room dividing hardware as manufactured by Sampson Mills Ltd.

1.02 SUBMITTALS

A. Product data: Manufacturer's descriptive literature shall be submitted, indicating materials, finishes and installation instructions for each type of window treatment specified.

B. Shop drawings: Components and installation detail drawings shall be supplied as requested.

C. Product selected as it removes the need for sewing, Velcro, nails, screws or glue for felt/fabric panels

C1. This is essential for easy onsite repair for the systems

C2. This Product reduces labor and offsite work as it has easy on site Hight adjustability.

C3. This System selected specifically because there is no front and back

C3a it looks identical from the window side (outside) or room side

C3b. It looks identical from both sides when used as room dividers.

D. The sliding carriers must have no more than 2 pivot points in order to allow it to travel through curves.

E. The carriers must be easily removable after the installation of the recessed profile is complete.

1.03 QUALITY ASSURANCE

A. Products shall be manufactured to meet or exceed all quality standards as stipulated by Sampson Mills.

B. Product specifically designed for labor reduction and for easy maintenance and repair. Quality and labor savings must be equal or greater approved solutions by manufacturer Sampson Mills.

1.04 DELIVERY, STORAGE AND HANDLING

A. Product shall be delivered to the project site in manufacturer's original packaging.

B. Product shall be handled and stored to prevent damage to materials, finishes and operating mechanisms.

C. Fabric and carriers shall be added to the track on site to avoid possible damage.

1.05 WARRANTY

A. Manufacturer shall provide that PF121R system components are free of defects for **Five** years from the date of shipping. Specific product warranty terms are available from Sampson Mills.

Part 2 -Product

2.01 MANUFACTURER

A. Acceptable product: Window treatment system, Room dividing #PF121R RECESSED HAND OPERATED FLAT PANEL TRACK as manufactured by:

Sampson Mills Ltd. P.O. Box 1147 New York, 10150

2.02 EQUIPMENT

A. Medium to heavy duty hand operated flat panel / room dividing track which shall accommodate Felt, Fabric, and other materials approved by manufacturer.

2.03 COMPONENTS

A. Track:

1. Shall be T6 anodized aluminum (optional: Sampson Mills approved powder coated finish) ,

1a Standard Colors Black, White, Silver

1b Custom colors available upon approval and request.

2. Curve-able on both inside and outside radii, to a minimum radius of 10"

3. Project site and drawings specifically designed for exterior dimensions of profiles Cad or pdf drawings available upon request.

4. Profiles and finishes must be rated for indoor & outdoor use.

B. Parts:

1. System shall include ceiling mount screws to install through the center of the track channel

2. Must use PP28 Profile protector when installing to insure no damage to the channels

2a. To be provided with every assembled order.

3. Must use PDB4 Philips drill bit to be provided with every assembled order.

4. System can also be installed with a nail gun into the flanges adhesive on the back of the track optional.



Sampson Mills Ltd.

Sampson Mills Ltd.
P.O. Box 1147
New York, 10150

Phone: (718) 412-9040
Fax: (718) 412-9039

info@Sampsonmills.com
www.Sampsonmills.com

5. Carriers for Felt to be either PFB120 or PFB90 for felt panels 8mm felt and above
6. Carriers for fabric to be either PFB120D or PFB90D for Fabric panels or 5mm felt and below
7. Shall be original Sampson Mills components.

C. Flat Panel Systems Options:

1. Standard Free-Flow Heading System (unlimited panels, limited to fit within the track width)

Part 3 -Execution

3.01 INSTALLATION

A. Install window treatment and room dividing system in accordance with Sampson Mills specifications, standards and procedures.

Installation contractor shall be responsible for site measurements and suitability of mounting surface.

B. Adequate clearance shall be provided to permit unencumbered operation of the entire system.

C. To prevent damage to the track, the Profile protector and Philips drill bit included with the track must be used during installation.

D. System can also be installed with a nail gun into the flanges adhesive on the back of the track optional.

E. When mudding in the track use 0.5" masking tape to protect the track channel from the plaster.

Manufacturer: Sampson Mills Ltd
718-412-9040
info@sampsonmills.com
PO Box 1147
New York NY 10150

technical counsel:
Joseph Bibi
718-412-9040; 415
Joseph@sampsonmills.com