

Sampson Mills Ltd. P.O. Box 1147 New York, 10150

Phone: (718) 412-9040 Fax: (718) 412-9039

info@Sampsonmills.com www.Sampsonmills.com

SPECIFICATION SAMPSON MILLS SYSTEM **#F120 HAND OPERATED CUBICLE DRAPERY TRACK**

Part 1 -General

1.01 SUMMARY

A. Work of this section includes hand operated window treatment and room dividing hardware as manufactured by Sampson Mills

1.02 SUBMITTALS

- A. Product data: Manufacturer's descriptive literature shall be submitted, indicating materials, finishes and installation instructions for each type of window treatment specified.
- B. Shop drawings: Components and installation detail drawings shall be supplied as requested.

1.03 QUALITY ASSURANCE

- A. Products shall be manufactured to meet or exceed all quality standards as stipulated by Sampson Mills.
- B. Product specifically designed for labor reduction and for easy maintenance and repair. Quality and labor savings must be equal or greater approved solutions by manufacturer Sampson Mils.

1.04 DELIVERY, STORAGE AND HANDLING

- A. Product shall be delivered to the project site in manufacturer's original packaging.
- B. Product shall be handled and stored to prevent damage to materials, finishes and operating mechanisms.

1.05 WARRANTY

A. Manufacturer shall provide that #F120 system components are free of defects for Five years from the date shipped. Specific product warranty terms are available from Sampson Mills.

Part 2 -Product 2.01 MANUFACTURER

A. Acceptable product: Window treatment system, #F120 HAND OPERATED DRAPERY TRACK as manufactured by: Sampson Mills Ltd. P.O. Box 1147 New York, 10150

2.02 COMPONENTS

A. Track:

- 1. Shall be T6 anodized aluminum (optional: Sampson Mills approved powder coated finish),
 - 1a Standard Colors Black, White, Silver
 - 1b Custom colors available upon approval and request.
- 2. Curve-able on both inside and outside radii, to a minimum radius of 10" For F120
- 3. Project site and drawings specifically designed for exterior dimensions of profiles Cad or pdf drawings available upon request.
- 4. Profiles and finishes must be rated for indoor & outdoor use.

B. Parts:

- 1. System can mount using SM suspension rods or side wall brackets, or "L" wall brackets for mounting.
- 2. Shall be original Sampson Mills components.

C. Drapery Heading Systems Options:

- 1. Standard Free-Flow Heading System
 - 1a. Shall be original Sampson Mills components or others approved by Sampson Mills.
- 2. Drapery S-Heading System
 - 2a. Shall be original Sampson Mills components or others approved by Sampson Mills.
- 3. Pinch Pleat Heading Systems:
 - 3a Shall be original Sampson Mills components or others approved by Sampson Mills.
- - 4a. Shall be original Sampson Mills components or others approved by Sampson Mills.
- 5. Must use suspension hardware provided by Sampson Mills
 - 5a. STW78 for sloped ceilings (tension wire)
 - 5b. STS78 for suspension ceilings (tension wire)
 - 5c. SPR for suspension ceilings (10 mm solid aluminum suspension rod)



Sampson Mills Ltd. P.O. Box 1147 New York, 10150

(718) 412-9040 Phone: (718) 412-9039 Fax:

info@Sampsonmills.com www.Sampsonmills.com

5d. SPD decorative suspension ceilings (10 mm solid aluminum suspension rod)

5e. Side wall mount WB12

5f. L bracket WBL4 (4"), Double bracket WBL8 (8") 5g. Drop ceiling ZC01 - Z clip for drop ceilings.

6. Shall be original Sampson Mills components.

Part 3 - Execution 3.01 INSTALLATION

A. Install window treatment system in accordance with Sampson Mills specifications, standards and procedures. Installation contractor shall be responsible for site measurements and suitability of mounting surface. B. Adequate clearance shall be provided to permit unencumbered operation of the entire system.

Manufacturer: Sampson Mills Ltd

718-412-9040

info@sampsonmills.com PO Box 1147

New York NY 10150

technical counsel:

Joseph Bibi

718-412-9040; 415

Joseph@sampsonmills.com